

# Terminal

The LoQit terminal is used to control and operate the LoQit electronic locking system. It contains a 10" touch screen covered with a glass plate, a multi card reader, a cloud controller and a Raspberry Pi. Power is supplied by means of an included power supply.

## Product descriptions

Product item	LoQit Terminal
Application	Control and operate the LoQit electronic locking system
Casting	Coated sheet metal
Plug type	5x RJ45   4 x USB-A   1x power supply
Power consumption of one terminal	Min. power consumption ca. 14VA (idle) Max. power consumption <60VA

## LoQit - Terminal

Lock model number	QTCE001
Brand name	LoQit
Origin	The Netherlands
HS code	8528 59 00

## Power Supply

Power Supply Number	QCPS201 24V/60VA
Brand name	Mean Well
Origin	Taiwan
Weight	272g
Spec sheet supplier	<a href="#">Link</a>
HS code	8544 42 90



## Mounting measurements



## Compliance

Category	Terminal
Standards	EN 61010-1, EN 61000-3-3, 55014-1, EN 55014-2
Connector	4x RJ45 LockController  1x RJ45 network  4 x USB-A   1x PIJ 24VDC
Weight	2500g (2772g with power supply) without packaging
Operating temperature	5 degrees to +55 degrees celcius
Storage temperature	5 degrees to +75 degrees celcius